

INVICTA TECHNICAL FILE

OPERATION, MAINTENANCE, & HEALTH AND SAFETY INSTRUCTIONS

PRODUCT RANGE/FORK MOUNTED SKIP COMPACTOR

Operation

1. Position the forks to the correct distance apart to locate into fork pockets.
2. Remove the safety lynch pin and fork pocket heel pins.
3. Drive the forks fully into the fork pockets.
4. Insert fork pocket heel pins directly behind the heel of the fork and attach safety lynch pin into hole provided.
5. Remove Height Adjustment Pin in the main vertical box section so as to adjust compactor height to suit waste/skip height.
6. Once desired position is achieved insert the Adjustment Pin into the aligned holes and attach safety lynch pin into hole provided.
7. The attachment is now ready for use.

Maintenance

1. The Fork Mounted Skip Compactor should be inspected weekly for general condition with particular attention paid to:
 - A – All weld points
 - B – Wear and distortion of Fork Pockets, Adjustment Pin and Heel Pins
 - C – Any damaged/worn components
2. Damage or failure must be reported and rectified immediately prior to re-use of the attachment.
3. General surface rusting especially in the critical areas should be treated with proprietary inhibitors, primers and paint on a regular basis.

Health and Safety

1. The Manager of the department or section where the compactor is to be used must be responsible for ensuring the operators are fully conversant with the unit, its operation, maintenance and that the heel pins are fitted correctly.
2. Ensure that the heel pins are correctly inserted, retained and positioned in relation to the heel of the fork prior to each and every use.
3. Do not drive into the fork pockets without removing the heel pins.
4. Always travel with the Compactor in its reduced position.
5. Ensure that the Adjustment Pin is retained in position with the Lynch Pin prior to each and every use.
6. Do not travel with the Compactor over rough terrain or carry out excessive cornering.
7. Do not shock load the truck/compactor under any circumstances.
8. Never exert lateral forces against compactor body.

The Operator should ensure that the above product is used for the purpose that it has been designed, tested and intended to do and no deviation to this occurs. If in doubt, consult your Fork Truck Dealer or approved Attachment Supplier.